



# PLYMAN

GREATER SELECTION • BETTER VALUE

## PRODUCT DATA SHEET

### Plyclad V Grooved Lining Plywood

- **Description:** Natural rotary peeled, wood veneer plywood sheets with V grooves to one face. Edge profile – grooved with plastic tongue.
- **Specie:** Radiata Pine
- **Size:** 2400 x 1207 (1200 cover)
- **Thickness, Construction Typical Weights**
  - 9mm 5 ply 14.0 kg
  - 12mm 5 ply 19.0 kg
- **Colours:** Pale cream
- **Texture:** Even texture, fine grain surface with V groove to one face. 100mm centres. 1.5mm deep x 3mm wide.
- **Source:** NZ plantation grown Radiata Pine. Classic grade suitable for a clear decorative finish.
- **Grades:** CD : General appearance face sanded two sides for paint or non decorative finish  
DD : Combination of open defects both sides sanded one face
- **Glue Bond:** A Bond - Marine Phenolic formaldehyde resin, 72 hour boil test. Commonly known as WBP (weather and boil proof) or A bond.
- **Workability:** Quality economic product reflecting high utilization of renewable timber resource. Produces strong, medium weight, stable panels. Machines, glues and finishes well.
- **Preservation:** Untreated : natural, non durable.  
LOSP : can be specified for exterior (clear) application.  
Not suitable for ground contact
- **Durability:** Non durable. Note that plywood is not required to be naturally durable. Thorough sealing with preservative compounds, paints or resins is necessary.
- **Uses:** A lining plywood to walls and ceilings.
- **Storage:** Keep dry, store undercover, stack clear of ground, on bearers

**NB.** Rotary peeled veneering yields veneers of all grades. Plywood faces are selected to a high quality but this is a volume production method which allows some surface roughness with occasional splits and checks. Comparison of slice cut veneers may give a false expectation as slice-cut veneers provide a smoother, tighter surface.