

PRODUCT DATA SHEET

Waveply (Bendy Plywood)

•	Description	Thick veneer face & back with thin opposite direction centre veneer. Open grained face and back allowing excellent flexibility. Available in Long Grain or Cross Grain construction.
•	Specie:	Fuma
•	Colour:	Light Straw/ Mid brown
•	Size:	2400x1200mm or 1200x2400mm
•	Thickness, Construction and Typical Weights:	4mm, 6mm & 9mm Selected thick faces with thin core and thermoset glues. Of 3 ply construction, choice of long grain or cross grain face direction. 4mm/5kg, 6mm/8kg, 9mm/10.7kg
•	Texture:	Open grained, medium texture. Grain opens more as sheets are curved.
•	Density:	490kg/m3
•	Source:	Africa/Fiji
•	Grade:	Interior Grade (Moisture resistant Glue line)
•	Gluing:	MR Thermoset glue.
•	Workability:	Easy to work with standard woodworking tools. Its benefit is in its bendability and once laminated will hold its shape.
•	Durability:	Non Durable but standard practices dictate that all faces and edges be sealed for moisture protection.
•	Uses:	Perfect for curved interiors, columns, furniture, marine interiors, commercial fitouts, etc

Ph: 0800 PLYMAN (0800 759 626) 70 The Concourse, Henderson, Auckland Email: info@plyman.co.nz

